

PRODUCT SPECIFICATIONS

STABLE BRAID™ COATED



Stable Braid has a braided core and cover, both contributing to its strength and firm hand, while remaining fully spliceable. It works very well on winch drums and has the non-rotational flexibility to be flaked on deck. Stable Braid is a proven, tough rope with excellent controlled working elongation.

FEATURES AND BENEFITS:

- > Durable
- > Easy to handle
- > Excellent abrasion resistance
- > Firm, yet flexible
- > Flex-fatigue resistant
- > Heat resistant
- > High strength-to-weight ratio
- > Low elastic elongation
- > Low stretch
- > Pro-Gard Marine Finish
- > Torque-free construction
- > UV resistant

APPLICATIONS INCLUDE:

- > General Working Line

PRODUCT CODE: 806

FIBER: Polyester / Polyester

SPECIFIC GRAVITY: 1.38

SPLICE/CLASS:

Double Braid Class I

ELASTIC ELONGATION:

At percent of break strength

10%1.10%

20%1.70%

30%2.70%

COLOR OPTIONS:

Coated black, blue, clear, green, orange, red, or yellow — all with blue ID



DIAM. (INCH)	CIRC. (INCH)	WEIGHT PER 100 FT. (LBS)	AVG. STRENGTH (LBS)	MIN. STRENGTH (LBS)
1	3	34	39,200	33,300
1 1/8	3 1/2	45.3	48,200	41,000
1 1/4	3 3/4	53.9	57,300	48,700
1 5/16	4	60.8	64,700	55,000
1 1/2	4 1/2	73.3	75,100	63,800
1 5/8	5	85.9	87,200	74,100



ISO strength specifications are for unspliced rope. All other strength specifications are for spliced rope.